


## Features


- Injection-molded PBT housing, UL-listed
- Integral self-closing metal laser protection flaps
- Long guiding section of connector body
- Split ceramic sleeve
- 1000 mating cycles
- Semi-transparent plastic dust cover, allowing optical testing with test lasers without removing the cover



090.7450

**i** Ceramic = zirconia ceramic alignment sleeve

Ordering Information	Description	PU	Part Number
 <p>030.5951</p>	<b>Adapter E-2000™ (screwable)</b> Adapter E-2000™ with semi-transparent dust caps. Quick mounting clip and M2 thread integrated.  <b>Scope of supply</b> – Adapter E-2000™ – 2 Philips head screws M2 x 8, blue galvanized		
	APC, green, ceramic SM, B	12	R846838
	APC, red, ceramic SM, B	12	R840222
	PC, blue, ceramic SM, B	12	R846841
	APC, green, ceramic, SM, C	12	R846577
	PC, blue, ceramic, SM, C	12	R846580
	PC, heather violet, ceramic MM, M	12	R847352
	PC, turquoise, ceramic MM, M	12	R847351
	PC, beige, ceramic MM, M	12	R847080
	PC, black, ceramic MM, M	12	R847081

 <p>030.5952</p>	<b>Adapter E-2000™ (flangeless)</b> Adapter E-2000™ flangeless with semi-transparent dust caps. Quick mounting clip integrated. Optimal front plate whickness: 1.3 mm / 1.7 mm		
	APC, green, ceramic SM, B	12	R846341
	PC, blue, ceramic SM, B	12	R846342
	APC, green, ceramic, SM, C	12	R846339
	PC, blue, ceramic, SM, C	12	R846340
	PC, heather violet, ceramic MM, M	12	R846576
	PC, turquoise, ceramic MM, M	12	R846345
	PC, beige, ceramic MM, M	12	R846343
	PC, black, ceramic MM, M	12	R846344