


Item no.	57054003-01		5/8M-TL540TI		
			CommScope QR 540 JCA		
Frequency Range	0.3 - 3000 MHz		Product photo		
Impedance (Nom.)	75 Ω				
	14.5 A @10°C increase				
(calculated)	20.5 A @20°C increase				
Transfer Impedance (CoMeT)	Class A++				
	<0.9 mΩ/m @ 5-30MHz				
	<0.06 mΩ/item @ 5-30MHz				
	Class A++				
Screening Attenuation(CoMeT)	Class A++				
	>130 dB @ 30-1000MHz				
	>130 dB @ 1000-2000MHz				
	>120 dB @ 2000-3000MHz				
Return Loss (IEC 61169-1)	Better than	Typical	Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-41 dB	-43.9 dB	0.3 - 500 MHz	-0.07 dB	-0.02 dB
500 - 860 MHz	-35 dB	-37.7 dB	500 - 860 MHz	-0.08 dB	-0.03 dB
860 - 1000 MHz	-33 dB	-35.5 dB	860 - 1000 MHz	-0.08 dB	-0.03 dB
1000 - 1750 MHz	-26 dB	-29.2 dB	1000 - 1750 MHz	-0.09 dB	-0.04 dB
1750 - 2150 MHz	-26 dB	-29.1 dB	1750 - 2150 MHz	-0.09 dB	-0.04 dB
2150 - 3000 MHz	-26 dB	-29.1 dB	2150 - 3000 MHz	-0.11 dB	-0.06 dB
Temperature			Intermodulation	IM3	
Installing	-5° to +50° C		3rd Order (@2x+37dBm)	-164 dBc	
Operating	-40° to +70° C				
Storing	-40° to +70° C		Inner Conductor Resistance (@ 1 A DC)	<0.6 mΩ	
Sealing Test (IEC IP-code)	IP X8 30 meter / 8 hours		Insulation Resistance (@ 500 VDC)	>200 GΩ	
O-rings	EPDM		Dielectric Strength DC Test Voltage	>3,5 KV	
Base Material			Max. Tensile Strength Overall	>1800 N	
Body Parts	Brass CuZn39Pb3		Inner Conductor	>500 N	
Inner Conductor	Brass CuZn39Pb3				
Plating			Torsional Strength (Connector / Cable)	* NATM	
Body Parts	Nitin-6				
Inner Conductor	Nitin-6		Test performed by	Sven-Erik Sandberg	
Insulators	COC (Topas) / PP with Glass		Date of release	January 08, 2015	
Remarks	* Not Able To Measure(NATM): The cable starts to twist without the connector losing its grip.				

All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
Further technical specifications and installation instructions can be obtained on request.